

Thickness measurement

MiniTest 403 /405



- Precision Ultrasonic Micrometer
- Rugged Quality Tool for rough industrial conditions
- Dual-element Transducer
- Measures various materials from 0.125 to 500mm (0.025 to 19.999 inches)
- Switch to select English or metric units
- Internal Data Logger (MiniTest 405)

High-speed scan!

ElektroPhysik's rugged thickness gauge family has been designed and built to satisfy the roughest industry conditions. The variety of features offered in the MiniTest 403 and MiniTest 405 allow the user to select a quality tool that will meet or exceed their specific application needs.

The gauges come in an all metal case and are sealed with gaskets to protect them from harsh working environments. The units are small and portable and will operate on 2 AA batteries for over 200 hours. You can take them anywhere to do the job.

Special features of the MiniTest 405 model

Internal data logger: Automatic numeric Data Logging system to store 1 to 1000 readings. OBST symbol to indicate no reading.

Differential mode: Enter acceptable thickness value, unit will display +/- the difference from the value entered.

Alarm mode: Enter a minimum acceptable thickness value. If measurement falls below minimum, red LED will illuminate and sound beeper. If measurement is above minimum value, green LED will illuminate.

Technical Data	
Measuring range:	0.63 to 500 mm / 0.025 to 19.999 inches in steel, depending on material and surface
Resolution:	0.01mm / 0.001 inch
Velocity range:	1250 to 10,000 m/sec / 0.0492 to .3937 in./µs
Measuring rate:	4 readings per sec. for single point measurements or 17 per sec. in Scan Mode - captures the minimum thickness
Calibration:	Single and two point calibration option included
Weight:	284 g / 10 ounces (with batteries)
Size:	64 x 121 x 32 mm / 2.5 x 4.75 x 1.25 inches / (W x H x D)
Operating temperature:	-30° to 50°C / -20° to 120°F /
Case:	extruded aluminium body with nickel-plated aluminium end caps (gasket sealed)
Keypad:	Sealed membrane resistant to both water and petroleum products. six or nine tactile-feedback keys.
Transducer:	Dual-element (transmit and receive) 1 to 10 MHz frequency range. Locking quick disconnect LEMO connectors. 4 foot cable. Custom transducers available for special applications.
Power source:	2 x 1.5V alkaline or 1.2V NiCad AA cells. Typically operates for 200 hours on alkaline and 130 hours on NiCad. Display flashes when battery is low. Unit turns off automatically when battery is too low to operate reliably.
Display:	Multi-function 4.5 digit liquid crystal display with 0.500 inch numerals, backlit for use in poor light conditions. Backlight is selectable on /off / auto (illuminates only when taking a measurement).
Data output: (available with MiniTest 405 only):	RS232 output sends data to a serial printer, a computer or other external storage device.

S.I. Instruments
256 South Rd. Hilton
South Australia 5033
Ph (08) 8352 5511

info@si-instruments.com
www.si-instruments.com



ElektroPhysik

ElektroPhysik
Pasteurstr. 15
D-50735 Köln
Tel.: +49(0)221 7520 4 0

ElektroPhysik USA
770 West Algonquin Rd.
Arlington Heights IL 60005
Phone: +1 847 437 6616

ElektroPhysik Nederland
Borgharenweg 140
6222 AA Maastricht
Tel.: +31(0)43 352 00 60

ElektroPhysik Belgium
Allée Marie Louise 4b
4121 Neupre
Tél.: +32(0)4 336 5205